



MATERIALS AND FINISH

SHELL : STEEL MATERIAL, TIN FINISHED
DIMPLES ON PLUG ONLY
CONNECTOR INSULATOR : PBT THERMOPLASTIC,
30% GLASS FILLED, UL 94V-0 RATED, BLACK COLOR
HIGH POWER CONTACT MATERIAL: BRASS, 3U"/5U"/10u" GOLD PLATED
LOW-POWER CONTACT MATERIAL: BRASS, 1U"/2u" GOLD PLATED

ELECTRICAL CHARACTERISTICS

SIGNAL CONTACT CURRENT RATING : 3 AMPS
SIGNAL CONTACT RESISTANCE : 1.0 MIILOHMS MAX.
HIGH POWER CONTACT CURRENT RATING :10,20,30R 40 AMPS
HIGH POWER CONTACT RESISTANCE : 2.7 MIILOHMS MAX.
DIELECTRIC WITHSTANDING VOLTAGE :
1000 V AC FOR 1 MINUTE
INSULATION RESISTANCE :5000 MEGAOHMS MIN.
TEMPERATURE RATING : -55°C ~ +125°C

NO	A	B	C	運轉地速	電流密度 (A)
2	1.7	2.5	4.5	1.47"10k	10A/PS
4	2.7	3.6	5.0	1.04"12k	20A/PS
6	3.4	4.4	5.5	8"10k	30A/PS
8	4.6	5.6	5.5	6"3k	40A/PS

[illegible]