



MATERIALS AND FINISH

SHELL : STEEL MATERIAL, TIN FINISHED
DIMPLES ON PLUG ONLY
CONNECTOR INSULATOR : PBT THERMOPLASTIC,
30% GLASS FILLED, UL 94V-0 RATED, BLACK COLOR
HIGH POWER CONTACT MATERIAL: COPPER, 30u"/50u"/10u" GOLD PLATED
LOW-POWER CONTACT MATERIAL: BRASS, 1u"/2u" GOLD PLATED

ELECTRICAL CHARACTERISTICS

SIGNAL CONTACT CURRENT RATING : 10/20/3.0 AMPS
SIGNAL CONTACT RESISTANCE : 10 MILLIOHMS MAX.
DIELECTRIC WITHSTANDING VOLTAGE :
1000 V AC FOR 1 MINUTE
INSULATION RESISTANCE : 2000 MEGAOHMS MIN.
TEMPERATURE RATING : -55°C ~ +125°C
COAXIAL CONTACT IMPEDANCE: 75 OHMS

ND	A±0.1	B±0.1	C±0.1	适配线数	电流强度(A)
2	1.7	2.5	4.5	14#~16#	10 AMPS
4	2.7	3.6	5.0	10#~12#	20AMPS
6	3.4	4.4	5.5	8#~10#	30AMPS
8	4.6	5.6	5.5	6#~8#	40AMPS
